

PRIMARY/SECONDARY WIRELESS PROTECTORBACKGROUND OF THE INVENTION

10 This invention relates generally to primary/secondary surge
5 protection devices for protecting telephone communications related
equipment from power and transient surges. More particularly, the
present invention relates to an improved primary/secondary surge
protector circuit for protecting telecommunication equipment from
power and transient surges occurring on the tip and/or ring conductors
of transmission lines connected thereto. Specifically, the primary/
secondary surge protector circuit of the instant invention includes
fusible links of a unique construction connected in series with a
primary voltage suppressor formed as a single unit on a printed
circuit board.

15 As is generally well-known to those skilled in the telecommuni-
cations industry, modern telecommunications equipment is susceptible
to transient surges such as those caused by lightning strikes and
other voltage surges on the transmission lines. Accordingly, primary
surge protector circuits are known in the prior art which have been
20 provided for connection to the incoming transmission lines so as to
be normally non-conductive but are rendered conductive when a voltage
surge exceeds a predetermined breakdown voltage (e.g., 250 V) for
protecting the equipment. However, it is also known that voltage
surges on the transmission lines which are well below the breakdown

voltage of the primary surge protector circuit may nevertheless create possible damage to the equipment. Thus, telecommunication equipment manufacturers have also typically provided some type of secondary surge protection in conjunction with the primary surge protector circuits.

As is shown in Figure 1, a prior art primary/secondary surge protector circuit includes a primary protector portion and a secondary protector portion. The primary protector portion is comprised of a primary voltage suppressor and a pair of bridle wires connected in series with the opposite ends of the voltage suppressor which are mounted on a printed circuit board. The bridle wires are either short pieces of gauged wire (e.g., #28 AWG size or less) or a fuse element. The bridle wires are required in order to meet or pass the primary test according to the specification set forth by UL Standards 497 and 497A. However, the use of the bridle wires in the form of short wires or fuse elements mounted on the printed circuit board has the disadvantages of increasing space requirements and costs. In addition, the bridle wires require the additional task of installation or assembly, thereby increasing manufacturing costs.

In view of these problems, the inventors have developed a way of replacing the short wires or fuse elements with fusible links consisting of tip and ring conductive traces of a unique construction formed on the printed circuit board.

SUMMARY OF THE INVENTION

Accordingly, it is a general object of the present invention to provide an improved primary/secondary surge protector circuit for protecting telecommunication equipment from power and transient surges which is relatively simple and economical to manufacture and assemble.

It is an object of the present invention to provide an improved primary/secondary surge protector circuit which meets the specifications set forth by UL Standards 497 and 497A.

It is still another object of the present invention to provide an improved primary/secondary surge protector circuit which includes fusible links of a unique construction connected in series with a primary voltage suppressor formed as a single unit on a printed circuit board in order to pass the primary test of the UL Standards 497 and 497A.

It is still yet another object of the present invention to provide an improved primary/secondary surge protector circuit which is characterized by a design wherein fusible links consisting of tip and ring conductive traces of a unique construction are formed on a printed circuit board.

In a preferred embodiment of the present invention, there is provided a primary/secondary surge protector circuit for protecting telecommunications equipment and the like from power and transient

surges which includes a printed circuit board and a surge protector circuit. The surge protector circuit is mounted on the printed circuit board. The printed circuit board has at least one tip conductor trace formed on its top surface and extending between an input tip terminal pin and a first internal node and has at least one ring conductive trace formed on its top surface and extending between an input ring terminal pin and a second internal node.

The surge protector circuit includes a voltage suppressor operative connected to the tip conductive trace at the first node and to the ring conductive trace at the second node. The tip and ring conductive traces define fusible links which are open when an excessive current is passed therethrough.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects and advantages of the present invention will become more fully apparent from the following detailed description when read in conjunction with the accompanying drawings with like reference numerals indicating corresponding parts throughout, wherein:

Figure 1 is a schematic circuit diagram of a prior art primary/secondary surge protector circuit;

Figure 2 is a schematic circuit diagram of another prior art primary/secondary surge protector circuit, similar to Figure 1, but further includes heat coils;

5 Figure 3 is a schematic circuit diagram of a primary/secondary surge protector circuit, constructed in accordance with the principles of the present invention;

Figure 4 is a schematic circuit diagram of a second embodiment of a primary/secondary surge protector circuit in accordance with the present invention;

10 Figure 5 is a simplified top plan view of a portion of a printed circuit board, illustrating certain ones of the conductive traces;

Figure 5a is an enlarged view of the encircled area 5a of Figure 5;

15 Figure 6 is an enlarged, cross-sectional view, taken along the lines 6-6 of Figure 5a;

Figure 7 is a simplified top plan view of a portion of a printed circuit board, illustrating an alternate embodiment of certain ones of the conductive traces;

20 Figure 7a is an enlarged view of the encircled area 7a of Figure 7; and

Figure 8 is an enlarged, cross-sectional view, taken along the lines 7-7 of Figure 7a.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

It is to be distinctly understood at the outset that the present invention shown in the drawings and described in detail in conjunction with the preferred embodiments is not intended to serve as a limitation upon the scope or teachings thereof, but is to be considered merely as an exemplification of the principles of the present invention.

Referring now in detail to the drawings, there is illustrated in Figure 1 a schematic circuit diagram of a prior art primary/secondary surge protector **10** for protecting telecommunications equipment from power and transient surges occurring on tip and/or ring conductors of transmission lines connected thereto. The surge protector circuit **10** is comprised of a primary protector portion **12** and a secondary protector portion **14**. The primary portion **12** of the surge protector circuit **10** includes first and second data signal conductors **16** and **18**. One end of the first conductor **16** is coupled to an input tip terminal pin **20** and its other end thereof is coupled to an output tip terminal pin **22**. Similarly, one end of the second conductor **18** is coupled to an input ring terminal pin **24** and its other end is coupled to an output ring terminal pin **26**.

The primary portion **12** of the surge protector circuit **10** includes a primary voltage suppressor **28** having a first lead **30** connected to the first conductor **16** at an internal node **32** and a second lead **34** connected to the second conductor **18** at an internal node **36**. A third lead **38** of the voltage suppressor **28** is connected to a ground potential. A first bridle wire **40** in the form of a short piece of gauged wire or fuse element is interconnected between the input tip terminal pin **20** and the internal node **32**. A second bridle wire **42** in the form of a short piece of gauged wire or fuse element is interconnected between the input ring terminal pin **24** and the internal node **36**.

The secondary portion **14** of the surge protector circuit **10** includes a pair of positive thermal coefficient (PTC) resistors **44**, **46**, a differential voltage suppressor **48**, and an isolation transformer **50**. The differential voltage suppressor **48** is connected in parallel across the primary windings **P** of the transformer **50** at nodes **50**, **54** respectively. The PTC resistor **44** has its ends interconnected between the output tip terminal pin **22** and the node **52**. The PTC resistor **46** has its ends interconnected between the output ring terminal pin **26** and the node **54**.

The secondary portion **14** further includes a secondary voltage suppressor **56** and a relay **58**. The secondary voltage suppressor **56** is connected in parallel across the secondary windings **S** of the transformer **50** at nodes **60**, **62** respectively. The relay **58** is interconnected between the respective nodes **60**, **62** and corresponding equipment

terminals **64**, **66** which are connected to the telephone communications equipment (not shown) to be protected.

As previously pointed out, in the primary protector portion **12** the primary voltage suppressor **28**, the first short piece of gauged wire or fuse element (bridle wire **40**) and the second short piece of gauged wire or fuse link (bridle wire **42**) are all mounted on a printed circuit board. As a result, the primary protector portion **12** suffers from the drawbacks of increased space requirements and higher costs. Further, the added task required for installing or assembling of the bridle wires **40**, **42** will also increase time-consuming labor costs during manufacturing.

In Figure 2, there is shown a schematic circuit diagram of another embodiment of a prior art primary/secondary surge protector circuit **210** for protecting the telecommunications equipment. The surge protector circuit **210** is comprised of a primary protector portion **212** and a secondary protector portion **214**. The primary portion of the surge protector circuit **210** includes first and second data conductors **216** and **218**. One end of the first conductor **216** is coupled to an input tip terminal pin **220** and its other end thereof is coupled to an output tip terminal pin **222**. Similarly, one end of the second conductor **218** is coupled to an input ring terminal pin **224** and its other end thereof is coupled to an output ring terminal pin **226**.

The primary portion **212** of the surge protector circuit **210** includes an primary voltage suppressor **228** having a first lead **230**

connected to the first conductor **216** at an internal node **232** and a second lead **234** connected to the second conductor **218** at an internal node **236**. A third lead **238** of the voltage suppressor **228** is connected to a ground potential. A first bridle wire **240** in the form of a short piece of gauged wire or fuse element is interconnected between the input tip terminal pin **220** and the internal node **232**. A second bridle wire **242** in the form of a short piece of gauged wire or fuse element is interconnected between the input ring terminal pin **224** and the internal node **236**. As thus far described, the primary portion **212** is identical to the primary portion **12** of Figure 1. In addition, the primary portion **212** includes a first heat coil **233** interconnected between the internal node **232** and the output tip terminal pin **222** and a second heat coil **237** interconnected between the internal node **236** and the output ring terminal pin **226**.

Since the secondary portion **214** is identical in its construction to the secondary portion **14** of Figure 1, it is believed unnecessary to describe in detail the same. However, it should be noted that the surge protector circuit **210** of Figure 2 suffers from all of the same disadvantages of the surge protector circuit **10** of Figure 1.

In order to overcome all of the problems associated with the surge protector circuits of Figures 1 and 2 but yet still pass the primary test according to the specifications set forth by UL Standards 497 and 497A, the inventors of the present invention have developed an improved primary/secondary surge protector circuit which includes fusible links of a unique construction for replacing the short pieces

of gauged wire or fuse elements shown in Figures 1 and 2. The fusible links take the physical form of tip and ring conductive traces which are especially designed to have predetermined width and height (thickness) dimensions. By varying the width and height dimensions of the conductive traces, the conductive traces can be made to correspond to any one of a number of wire gauge sizes, such as #28 AWG size or less, respectively. The conductive traces will create a discontinuity or open up when heated due to an excessive current being passed through it.

With reference now to Figure 3 of the drawings, there is depicted a schematic circuit diagram of an improved primary/secondary surge protector circuit **310** for protecting telecommunications equipment from power and transient surges occurring on tip and/or ring conductors of transmission lines connected thereto, constructed in accordance with the principles of the present invention. The surge protector circuit **310** is comprised of a primary protector portion **312** and a secondary protector portion **314**. The primary portion **312** of the surge protector circuit **310** includes first and second data signal conductors **316** and **318**. One end of the first conductor **316** is coupled to an input tip terminal pin **320** and its other end thereof is coupled to an output tip terminal pin **322**. Similarly, one end of the second conductor **318** is coupled to an input ring terminal pin **324** and its other end thereof is coupled to an output ring terminal pin **326**.

The primary portion **312** of the surge protector circuit **310** includes a primary voltage suppressor **328** having a first lead **330**

connected to the first conductor **316** at an internal node **332** and a second lead **334** connected to the second conductor **318** at an internal node **336**. A third lead **338** of the voltage suppressor **328** is connected to a ground potential. A first fusible link **340** in the form of tip
5 conductive trace is interconnected between the input terminal pin **320** and the internal node **332**. A second fusible link **342** in the form of a ring conductive trace is interconnected between the input ring terminal **324** and the internal node **336**. All of the electrical components between the input terminals **320**, **324** and the output terminals
10 **322**, **326** are formed as a single unit on a printed circuit board.

The primary voltage suppressor **328** may be formed of a silicon avalanche suppressor (SAS), sidactor, gas discharge tube or other similar devices which have predetermined breakdown voltages that are relatively high, preferably in the range of approximately 200-600
15 volts. In the preferred embodiment, the primary voltage suppressor **328** is a silicon avalanche suppressor similar to type 1.5 KE.

The secondary portion **314** of the surge protector circuit **310** is identical in its construction to the secondary portion **14** of Figure 1. In particular, the secondary portion **314** of the surge protector
20 circuit **310** includes a pair of positive thermal coefficient (PTC) resistors **344**, **346**, a differential voltage suppressor **348**, and an isolation transformer **350**. The differential voltage suppressor **348** is connected in parallel across the primary windings **P** of the transformer **350** at nodes **352**, **354** respectively. The PTC resistor **344** has
25 its ends interconnected between the output tip terminal pin **322** and

the node **352**. The PTC resistor **346** has its ends interconnected between the output ring terminal pin **326** and the node **354**.

The secondary portion **314** further includes a secondary voltage suppressor **356** and a relay **358**. The secondary voltage suppressor **356** is connected in parallel across the secondary windings **S** of the transformer **350** at nodes **360**, **362** respectively. The relay **358** is interconnected between the respective nodes **360**, **362** and corresponding equipment terminals **364**, **366** which are connected to the telephone communications equipment (not shown) to be protected.

The unique construction of the fusible links **340** and **342** formed on a printed circuit board is best understood by reference to Figures 5, 5a and 6. As can be seen from Figures 5 and 5a, the fusible links **340** and **342** are identical in their construction and take the physical form of respective tip and ring conductive traces which are located on the top surface of a printed circuit board **500**. The tip conductive trace **340** extends between the input tip terminal pin **320** and the internal node **332**. Similarly, the ring conductive trace **342** extends between the input ring terminal pin **324** and the internal node **336**. Each of the tip and ring conductive traces **340**, **342** has a uniform width **W** and height **H** along the path between the respective input terminal pins and the corresponding internal nodes.

In Figure 6, there is shown an enlarged cross-sectional view of the ring conductive trace **342** taken along the lines 6-6 of Figure 5a. It will be noted that the width **W** has typically a dimension of ap-

proximately .040 inches, and the height **H** has a dimension of approxi-
mately .0028 inches so as to correspond to approximately a #28 AWG
size. However, it should be clearly understood to those skilled in
the art that the width and length dimensions can be varied as desired
5 so as to correspond to any one of a number of gauged wire sizes.

10
15
With reference now to Figure 4 of the drawings, there is illus-
trated a schematic circuit diagram of a second embodiment of an
improved primary/secondary surge protector circuit **410** for protecting
the telecommunication equipment in accordance with the present
invention. The surge protector circuit **410** is comprised of a primary
protector portion **412** and a secondary protector portion **414**. The
primary portion of the surge protector circuit **410** includes first and
second data signal conductors **416** and **418**. One end of the first con-
ductor **416** is coupled to an input tip terminal pin **420** and its other
end thereof is coupled to an output tip terminal pin **422**. Similarly,
one end of the second conductor **418** is coupled to an input ring
terminal pin **424** and its other end thereof is coupled to an output
ring terminal pin **426**.

20
25
The primary portion **412** of the surge protector **410** includes a
primary voltage suppressor **428** having a first lead **430** connected to
the first conductor **416** and an internal node **432** and a second lead **434**
connected to the second conductor **418** at an internal node **436**. A
third lead **438** of the voltage suppressor **428** is connected to a ground
potential. A first fusible link **440** in the form of a tip conductive
trace is interconnected between the input tip terminal pin **420** and the

internal node **432**. A second fusible link **442** in the form of a ring conductive trace is interconnected between the input ring terminal pin **424** and the internal node **436**.

As thus far described, the primary portion **412** is identical to the primary portion **312** of Figure 3. In addition, the primary portion **412** includes a first heat coil **433** interconnected between the internal node **432** and the output tip terminal pin **422** and a second heat coil **437** interconnected between the internal node **436** and the output ring terminal pin **426**. Since the secondary portion **414** is identical in its construction to the secondary portion **314** of Figure 3, it is believed unnecessary to describe in detail the same.

The unique construction of the fusible links **440** and **442** formed on a printed circuit board is best understood by reference to Figures 7, 7a and 8. As can be seen from Figures 7 and 7a, the fusible links **440** and **442** are identical in their construction and take the physical form of respective tip and ring conductive traces which are located on the top surface of a printed circuit board **700**. The tip conductive trace **440** extends between the input terminal pin **420** and the internal node **432**. Similarly, the ring conductive trace **442** extends between the input ring terminal pin **424** and the internal node **436**. Unlike the tip and ring conductive traces **340**, **342** of Figures 5, 5a and 6 having a uniform width and height throughout, the conductive traces **440**, **442** have a respective reduced or necked-down section **440a**, **442a** which has a narrow width **W'** disposed substantially intermediate of wider sections **440b**, **442b** and **440c**, **442c**.

In Figure 8, there is shown an enlarged cross-sectional view of the ring conductive trace **442**, taken along the lines 7-7 of Figure 7a. It will be noted that the width **W'** in the necked-down sections **442a** has typically a dimension of approximately .020 inches and the height **H'** has a dimension of approximately .0028 inches. However, it should again be clear to those skilled in the art that the width and length dimensions can be varied as desired so as to correspond to a particular gauged wire size.

From the foregoing detailed description, it can thus be seen that the present invention provides an improved primary/secondary surge protector circuit for protecting telecommunication equipment and the like from power surges which includes a printed circuit board and a surge protector circuit. The surge protector circuit is mounted on the printed circuit board. The printed circuit board has tip and ring conductive traces formed on its top surface so as to define fusible links which are opened when an excessive current is passed therethrough. The conductive traces are dimensioned so as to pass the primary test according to the specifications set forth by UL Standards 497 and 497A.

While there has been illustrated and described what is at present considered to be a preferred embodiment of the present invention, it will be understood by those skilled in the art that various changes and modifications may be made, and equivalents may be substituted for elements thereof without departing from the true scope of the invention. In addition, many modifications may be made to adapt a

particular situation or material to the teachings of the invention without departing from the central scope thereof. Therefore, it is intended that this invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out the invention, but that the invention will include all embodiments falling within the scope of the appended claims.

5

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216